

EAST Search History

Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
S3	47	((("0437965") or ("1876990") or ("2396040") or ("2410971") or ("2439980") or ("2491325") or ("2525379") or ("2768547") or ("2797564") or ("2933959") or ("2968979") or ("2984133") or ("3001430") or ("3292678") or ("3535958") or ("3890859") or ("4041811") or ("4063474") or ("4238978") or ("4249435") or ("4517865") or ("4774864") or ("4901610") or ("5123289") or ("5239875") or ("5337638") or ("5746298") or ("6095020") or ("6029551") or ("6155147") or ("6358152") or ("6361259"))).PN.	USPAT; USOCR	OR	OFF	2005/07/29 15:45
S5	69	(81/480).CCLS.	USPAT; USOCR; EPO; JPO	OR	OFF	2005/11/11 09:51
S6	41	(81/472).CCLS.	USPAT; USOCR; EPO; JPO	OR	OFF	2005/08/03 11:25
S7	113	(81/473).CCLS.	USPAT; USOCR; EPO; JPO	OR	OFF	2005/11/11 09:50
S8	352	(81/467).CCLS.	USPAT; USOCR; EPO; JPO	OR	OFF	2005/08/03 11:23
S9	0	"09388720"	US-PGPUB; USPAT; USOCR; EPO; JPO	OR	ON	2005/08/01 16:15
S10	14	"ludwig et al" and screwdriver	US-PGPUB; USPAT; USOCR; EPO; JPO	OR	ON	2005/08/01 16:15
S11	1	("4655103").PN.	US-PGPUB; USPAT; USOCR; EPO; JPO	OR	OFF	2005/08/01 16:25
S12	264	(81/475).CCLS.	USPAT; USOCR; EPO; JPO	OR	OFF	2005/08/03 10:11
S13	5	("torque limiting tool").clm.	US-PGPUB; USPAT; USOCR; EPO; JPO	OR	ON	2005/08/03 10:11

EAST Search History

S14	125	(81/480 81/472 81/473 81/467) and (inch or millimeter or cetimeter or mm or cm)	US-PGPUB; USPAT; USOCR; EPO; JPO	OR	ON	2005/08/03 11:27
S15	34428	("screwdriver" "screw driver" "driver" "tool") with (torque)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	OR	ON	2005/11/11 09:52
S16	12123	("screwdriver" "screw driver" "driver" "tool") with (torque with (limit\$4 maxim\$4 minim\$4 regulat\$4 control\$4))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	OR	ON	2005/11/11 09:53
S17	23	(screwdriver with handle with spring with torque)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	OR	ON	2005/11/11 10:04
S18	27571	torque near3 limit\$4	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	OR	ON	2005/11/11 10:36
S19	1274	(torque near3 limit\$4) with tool	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	OR	ON	2005/11/11 10:30
S20	738	(torque near3 limit\$4) with tool and spring	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	OR	ON	2005/11/11 10:30
S21	411	(torque near3 limit\$4) with tool and spring and (groove channel ridge trough)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	OR	ON	2005/11/11 10:31
S23	141	(torque near3 limit\$4) and (bias near3 (axial\$4 longitudinal\$4))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	OR	ON	2005/11/11 10:38
S25	427	(torque near3 limit\$4) and (radial\$4 near3 displace\$4)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	OR	ON	2005/11/11 10:39

EAST Search History

S26	10	S23 and S25	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	OR	ON	2005/11/11 10:40
S27	705	(torque adj limit\$3) near3 (ratchet wrench driver screwdriver handle tool)	US-PGPUB; USPAT; USOCR; EPO; JPO	OR	ON	2006/03/01 18:51
S28	158	S27 and (plastic polymer\$3 polyurethane)	US-PGPUB; USPAT; USOCR; EPO; JPO	OR	ON	2006/03/01 18:52